FJ-02VAADDB

HELIAX® Discrete MULTIMODEFIBER JUMPER Cca ARMOR NBOOT..

Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

Product Type Wireless Fiber Cable Assemblies

Product Brand HELIAX®

Product Series FJ

Ordering Note ANDREW® non-standard product

General Specifications

Color, connector AAquaColor, connector BAqua

Construction Type Discrete fiber tail

Interface, Connector A DLC

 Interface Feature, connector A
 Standard

 Interface Body Style, connector A
 Straight

 Interface, Connector B
 DLC

 Interface Feature, connector B
 Outdoor

 Interface Body Style, connector B
 Straight

 Jacket Color
 Black

Total Fibers, quantity 2

Dimensions

Cable Assembly Length Range (m) 3 - 5

Diameter Over Jacket 5 mm | 0.197 in

Mechanical Specifications

Minimum Bend Radius 20 mm | 0.787 in

Optical Specifications



FJ-02VAADDB

Fiber Mode Multimode

Fiber Type OM4, bend insensitive

Insertion Loss, typical note Insertion loss is measured at 1310 and 1550 nm

Insertion Loss, typical 0.5 dB

Environmental Specifications

Operating Temperature $-40 \,^{\circ}\text{C} \text{ to } +70 \,^{\circ}\text{C} \, (-40 \,^{\circ}\text{F to } +158 \,^{\circ}\text{F})$

Environmental Space Outdoor

Packaging and Weights

Cable weight 35 kg/km | 23.519 lb/kft

* Footnotes

Insertion Loss, typical note Insertion loss is measured at a room temp of +20°C (+68°F)

