F4C-HPHMNM-4M



HELIAX® 1/2" SureFlex® Jumper with interface types 4.3-10 Male and N Male, 4m

• WARNING: DO NOT MATE WITH 4.1-9.5 DIN

Product Classification

Dreduct Ture	SureFlave UD UFUAVe partermanae	
Product Type	SureFlex® HP, HELIAX® performance	
Product Brand	HELIAX® SureFlex®	
Product Series	RSJ4-50	
General Specifications		
Body Style, Connector A	Straight	
Body Style, Connector B	Straight	
Interface, Connector A	4.3-10 Male	
Interface, Connector B	N Male	
Specification Sheet Revision Level	А	
Dimensions		
Length	4 m 13.123 ft	
Nominal Size	1/2 in	
Electrical Specifications		
3rd Order IMD Static Test Method	Two +43 dBm carriers	
3rd Order IMD, typical	-112 dBm	
DTF, Connector A	-34 dB	
DTF, Connector B	-34 dB	
VSWR/Return Loss		

Frequency Band	VSWR, typical	Return Loss, typical (dB)
698–960 MHz	1.065	30
1700–2200 MHz	1.065	30
2200–2700 MHz	1.106	26

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 19, 2025

F4C-HPHMNM-4M

Jumper Assembly Sample Label



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 19, 2025

Page 2 of 2