
FP-01SDDCGSDD



Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

Product TypeWireless Fiber Cable Assemblies

Product Brand HELIAX®

Product Series FP

Ordering Note ANDREW® non-standard product

General Specifications

Color, connector ABlueColor, connector BBlue

Construction Type Simplex patch cord

Interface, Connector A

LC/UPC

Interface Body Style, connector A

Straight

Interface, Connector B

SC/UPC

Interface Body Style, connector B

Straight

Jacket Color

Yellow

Total Fibers, quantity 1

Dimensions

Cable Assembly Length Range (m) 1 – 15

Diameter Over Jacket 1.6 mm | 0.063 in

Optical Specifications

Fiber ModeSinglemodeFiber TypeG.657.A2

Insertion Loss, typical note Insertion loss is measured at 1310 and 1550 nm

Insertion Loss, typical 0.5 dB



FP-01SDDCGSDD

Environmental Specifications

Operating Temperature $-10 \,^{\circ}\text{C} \text{ to } +60 \,^{\circ}\text{C} \text{ (+14 }^{\circ}\text{F to } +140 \,^{\circ}\text{F)}$

Environmental Space Indoor

* Footnotes

Insertion Loss, typical note Insertion loss is measured at a room temp of +20°C (+68°F)

