

HJBE02IBDAAAAN



HELIAX® Hybrid Jumper Singlemode B2ca Red/White 2 cores 1.5 mm2
Blunt Cut/Blunt Cut 4 fibers DLC to DLC Breakout length DC/FIBER
170mm No weatherproofing shroud.

Product Classification

Regional Availability	Asia Australia/New Zealand China EMEA Europe India Latin America Middle East/Africa North America
Product Type	Hybrid cable assembly
Product Brand	HELIAX®
Ordering Note	ANDREW® non-standard product

General Specifications

Conductors, quantity	2
Construction Type	Hybrid standard tail
Interface, Connector A	DLC
Interface Feature, connector A	Standard
Interface Body Style, connector A	Flex angle
Interface, Connector B	DLC
Interface Feature, connector B	Standard
Interface Body Style, connector B	Flex angle
Jacket Color	Black
Total Fibers, quantity	2

Dimensions

Breakout Length, connector A	170 mm 6.693 in
Breakout Length, connector B	170 mm 6.693 in
Cable Assembly Length Range (ft)	1 – 200
Diameter Over Jacket	11.7 mm 0.461 in
Center Conductor Gauge	1.5 mm²

Mechanical Specifications

Minimum Bend Radius	117 mm 4.606 in
---------------------	-------------------

HJBE02IBDAAAAN

Minimum Bend Radius, furcation 30 mm | 1.181 in

Optical Specifications

Fiber Mode Singlemode

Fiber Type G.657.A2

Insertion Loss, typical note Insertion loss is measured at 1310 and 1550 nm

Insertion Loss, typical 0.5

Environmental Specifications

Operating Temperature -40 °C to +75 °C (-40 °F to +167 °F)

Packaging and Weights

Cable weight 0.086 kg/m | 0.058 lb/ft

* Footnotes

Insertion Loss, typical note Insertion loss is measured at a room temp of +20°C (+68°F)