


F4CLAMP-CNL-E1B



KwikClamp™ Hanger for 1/2 in superflexible coaxial cable, single stack, C-Channel compatible; includes hardware

Product Classification

Product Type	Hanger kit
Product Brand	KwikClamp™
Ordering Note	ANDREW® standard product in Europe, the Middle East, and Africa Minimum order quantity (MOQ) is 1 box

General Specifications

Cables per Hanger	1
Color	Black
Hanger Type	KwikClamp™ hanger
Mounting	Channel section 40 x 22 x 1.5 mm

Dimensions

Height	111 mm 4.37 in
Width	31 mm 1.22 in
Length	42 mm 1.654 in
Compatible Diameter, maximum	14 mm 0.551 in
Compatible Diameter, minimum	13 mm 0.512 in
Nominal Size	1/2 in
Hanger Spacing, maximum	1.83 m 6.004 ft

Electrical Specifications

Return Loss Effect, maximum	0.1 dB
DTF Effect, maximum	0.1 dB

Material Specifications

Material Type	Engineered plastic Stainless steel
----------------------	--------------------------------------

Mechanical Specifications

F4CLAMP-CNL-E1B

Vibration Survival

≥4 hours at resonant frequency

Environmental Specifications

Operating Temperature

-40 °C to +70 °C (-40 °F to +158 °F)

Corrosion Resistance, minimum with no degradation

≥500 hours in salt spray chamber

Environmental Strength Capability

Five times cable weight

UV Resistance, minimum with no degradation

≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

Height, packed

30 cm | 11.811 in

Width, packed

30.5 cm | 12.008 in

Length, packed

22 cm | 8.661 in

Included

Hardware

Packaging quantity

100

Weight, gross

7 kg | 15.432 lb