


L4A-PNMDM

Base Product



OBSOLETE

This product was discontinued on: April 1, 2014

Replaced By:

L4A-NFDF-1M-P	LDF4-50A SureFlex® Jumper with interface types N Female and 7-16 DIN Female, 1 m
L4A-NFDF-2M-P	LDF4-50A SureFlex® Jumper with interface types N Female and 7-16 DIN Female, 2 m
L4A-NFDF-3M-P	LDF4-50A SureFlex® Jumper with interface types N Female and 7-16 DIN Female, 3 m
L4A-NFDF-5M-P	LDF4-50A SureFlex® Jumper with interface types N Female and 7-16 DIN Female, 5 m
L4A-NFDM-1M-P	LDF4-50A SureFlex® Jumper with interface types N Female and 7-16 DIN Male, 1 m
L4A-NFDM-2M-P	LDF4-50A SureFlex® Jumper with interface types N Female and 7-16 DIN Male, 2 m
L4A-NFDM-3M-P	LDF4-50A SureFlex® Jumper with interface types N Female and 7-16 DIN Male, 3 m
L4A-NFDM-5M-P	LDF4-50A SureFlex® Jumper with interface types N Female and 7-16 DIN Male, 5 m
L4A-NMDF-P	LDF4-50A SureFlex® Jumper with interface types N Male and 7-16 DIN Female, variable length
L4A-NMDM-12M-P	LDF4-50A SureFlex® Jumper with interface types N Male and 7-16 DIN Male, 12 m
L4A-NMDM-15M-P	LDF4-50A SureFlex® Jumper with interface types N Male and 7-16 DIN Male, 15 m
L4A-NMDM-18M-P	LDF4-50A SureFlex® Jumper with interface types N Male and 7-16 DIN Male, 18 m
L4A-NMDM-1M-P	LDF4-50A SureFlex® Jumper with interface types N Male and 7-16 DIN Male, 1 m
L4A-NMDM-1M5-P	LDF4-50A SureFlex® Jumper with interface types N Male and 7-16 DIN Male, 1.5 m
L4A-NMDM-2M-P	LDF4-50A SureFlex® Jumper with interface types N Male and 7-16 DIN Male, 2 m
L4A-NMDM-3M-P	LDF4-50A SureFlex® Jumper with interface types N Male and 7-16 DIN Male, 3 m
L4A-NMDM-5M-P	LDF4-50A SureFlex® Jumper with interface types N Male and 7-16 DIN Male, 5 m
L4A-NMDM-7M-P	LDF4-50A SureFlex® Jumper with interface types N Male and 7-16 DIN Male, 7 m
L4A-NMDM-9M-P	LDF4-50A SureFlex® Jumper with interface types N Male and 7-16 DIN Male, 9 m
L4A-NMDM-P	LDF4-50A SureFlex® Jumper with interface types N Male and 7-16 DIN Male, variable length
L4A-NMDR-P	LDF4-50A SureFlex® Jumper with interface types N Male and 7-16 DIN Male right, variable length

L4A-PNMDM

Product Classification

Product Type	Wireless transmission cable assembly
Product Brand	HELIAX® SureFlex®
Product Series	LDF4-50A

General Specifications

Body Style, Connector A	Straight
Body Style, Connector B	Straight
Interface, Connector A	N Male
Interface, Connector B	7-16 DIN Male
Specification Sheet Revision Level	A
Variable Length	For custom lengths, contact your local ANDREW representative

Dimensions

Length	0 m 0 ft
Nominal Size	1/2 in

Electrical Specifications

DTF, Connector A	-32 dB
DTF, Connector B	-32 dB

Jumper Assembly Sample Label

L4A-PNMDM



Environmental Specifications

Immersion Test Method Meets IEC 60529:2001, IP68 in mated condition