F1A-PNRDR-30N



Product Classification

Product Type SureFlex® standard

Product Brand HELIAX® | SureFlex®

Product Series FSJ1-50A

General Specifications

Body Style, Connector ARight angleBody Style, Connector BRight angleInterface, Connector AN Male

Interface, Connector B 7-16 DIN Male

Orientation 0° Specification Sheet Revision Level A

Dimensions

Length 0.76 m | 2.493 ft

Nominal Size 1/4 in

VSWR/Return Loss

Frequency Band VSWR Return Loss (dB)

700–3000 MHz 1.33 17

Jumper Assembly Sample Label



F1A-PNRDR-30N



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Agency	Classification
Adency	Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

Included Products

35422-33	_	Heat Treated FSJ1-50A, HELIAX® Superflexible Low Density Foam Coaxial Cable, corrugated copper, 1/4 in, black PE Jacket
35422-75	-	Heat Treated FSJ1RK-50B, HELIAX® Superflexible Foam Coaxial Cable, corrugated copper, 1/4 in, black non-halogenated, fire retardant polyolefin jacket
FSJ1-50A	-	FSJ1-50A, HELIAX® Superflexible Low Density Foam Coaxial Cable, corrugated copper, 1/4 in, black PE jacket
FSJ1RK-50A	-	FSJ1-50A, HELIAX® Superflexible Foam Coaxial Cable, corrugated copper, 1/4 in, black non-halogenated, fire retardant polyolefin jacket, B2ca s1a dO a1 Compliant

