F1A-XMHM-3-P

FSJ1-50A SureFlex® Jumper with interface types NEX10 Male and 4.3-

• WARNING: DO NOT MATE WITH 4.1-9.5 DIN

Product Classification

Product Type		SureFlex® Premium, static PIM	
Product Brand		HELIAX® SureFlex®	
Product Series		FSJ1-50A	
General Specifications			
Body Style, Connector A		Straight	
Body Style, Connector B		Straight	
Interface, Connector A		NEX10 Male	
Interface, Connector B		4.3-10 Male	
Specification Sheet Revision Level		А	
Dimensions			
Length		0.914 m 2.999 ft	
Nominal Size		1/4 in	
Electrical Specifications			
3rd Order IMD		-116 dBm	
3rd Order IMD Test Method		Two +43 dBm carriers	
VSWR/Return Loss			
Frequency Band	VSWR	Return Loss	

Frequency Band	VSWR	Return Loss (dB)
698–970 MHz	1.065	30
1700–2200 MHz	1.083	28
2200–2700 MHz	1.106	26
3400–3800 MHz	1.222	20

Jumper Assembly Sample Label

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

F1A-XMHM-3-P



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 2 of 2