F1R-NMNM-3M-P

FSJ1RK-50B SureFlex® Jumper with interface types N Male and N Male,



■ 3 m

Product Classification

Product Type SureFlex® Premium, static PIM

Product Brand HELIAX® | SureFlex®

Product Series FSJ1-50B

General Specifications

Body Style, Connector A Straight
Body Style, Connector B Straight
Interface, Connector A N Male
Interface, Connector B N Male
Specification Sheet Revision Level A

Dimensions

Length 3 m | 9.843 ft

Nominal Size 1/4 in

Electrical Specifications

3rd Order IMD Static -107 dBm

3rd Order IMD Static Test MethodTwo +43 dBm carriers

VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
698-960 MHz	1.15	23.13
1700-2200 MHz	1.15	23.13
2200-2700 MHz	1.152	23.02

Jumper Assembly Sample Label





Environmental Specifications

EN50575 CPR Cable EuroClass Fire PerformanceB2caEN50575 CPR Cable EuroClass Smoke Rating\$1aEN50575 CPR Cable EuroClass Droplets Ratingd0EN50575 CPR Cable EuroClass Acidity Ratinga1

Immersion Test MethodMeets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

