F1A-HMHR-45-TMB



WARNING: DO NOT MATE WITH 4.1-9.5 DIN

Product Classification

Product Type SureFlex® standard

Product Brand HELIAX® | SureFlex®

Product Series FSJ1-50A

General Specifications

Body Style, Connector AStraightBody Style, Connector BRight angleInterface, Connector A4.3-10 MaleInterface, Connector B4.3-10 Male

Specification Sheet Revision Level A

Dimensions

Length 13.716 m | 45 ft

Nominal Size 1/4 in

Electrical Specifications

3rd Order IMD -117 dBm

3rd Order IMD Test Method Two +43 dBm carriers

VSWR/Return Loss

| Frequency Band | VSWR | Return Loss (dB) |
|----------------|-------|------------------|
| 698-2700 MHz | 1.152 | 23.02 |
| 3400-3800 MHz | 1.288 | 18 |
| 3800-6000 MHz | 1.288 | 18 |

Jumper Assembly Sample Label



F1A-HMHR-45-TMB



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Agency

Classification

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

Included Products

FSJ1-50A

FSJ1-50A, HELIAX® Superflexible Low Density Foam Coaxial Cable, corrugated copper, 1/4 in, black PE jacket

