ATCB-B01-RM50



RET control cable with Straight Female AISG connector and Right Angle Male AISG connector key at nine o'clock position

• Feeds data and power to RET system components

OBSOLETE

This product was discontinued on: March 27, 2020

Product Classification

Product Type	AISG right angle
General Specifications	
AISG Connector A	8-pin DIN Female
AISG Connector A Body Style	Straight
AISG Connector A Standard	IEC 60130-9
AISG Connector B	8-pin DIN Male
AISG Connector B Body Style	Right angle
AISG Connector B Standard	IEC 60130-9
Color	Black
Data Conductor Type	0.24 mm² (24 AWG) twisted pair
EU Certification	CB CE
Power Conductor Type	0.82 mm² (18 AWG) stranded
Dimensions	
Length	0.5 m 1.64 ft
Diameter Over Jacket	8 mm 0.315 in
Electrical Specifications	
Protocol	AISG 1.1 AISG 2.0
Voltage, maximum	300 V

Environmental Specifications

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 12, 2025

ATCB-B01-RM50

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Relative Humidity	Up to 100%
Climatic Sequence Test Method	IEC 60068-2-14
Corrosion Test Method	IEC 60068-2-11, Test Condition Ka
Ingress Protection Test Method	IEC 60529:2001, IP67
UV Resistance Test Method	IEC 60068-2-5, Test Condition B

Regulatory Compliance/Certifications

Classification

ISO 9001:2015

Agency

Designed, manufactured and/or distributed under this quality management system

