

# LS2-JMHM-D

Base Product



D-CLASS LSF2-50 SureFlex® Jumper with interface types 2.2-5 Male and 4.3-10 Male, variable length

- WARNING: DO NOT MATE WITH 4.1-9.5 DIN

## Product Classification

Product Type	Wireless transmission cable assembly
Product Series	LSF2-50

## General Specifications

Body Style, Connector A	Straight
Body Style, Connector B	Straight
Interface, Connector A	2.2-5 Male
Interface, Connector B	4.3-10 Male
Specification Sheet Revision Level	A
Variable Length	For custom lengths, contact your local ANDREW representative

## Dimensions

Nominal Size	3/8 in
--------------	--------

## Logo Image

# LS2-JMHM-D



## Electrical Specifications

3rd Order IMD Dynamic	-119 dBm
3rd Order IMD Dynamic Test Method	Two +43 dBm carriers per IEC 62037

## VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
698–970 MHz	1.065	30.04
1700–2200 MHz	1.065	30.04
2200–2700 MHz	1.083	27.99
3400–3800 MHz	1.222	20.01
4000–6000 MHz	1.222	20.01

## Jumper Assembly Sample Label

# LS2-JMHM-D



## Environmental Specifications

**Immersion Test Method** Meets IEC 60529:2001, IP68 in mated condition

## Included Products

- |          |   |   |
|----------|---|---|
| LS2JM-S2 | - | 2.2-5 Male for 3/8 in LSF2-50 cable, factory attached   |
| LSF2-50  | - | LSF2-50, HELIAX® Superflexible Foam Coaxial Cable, corrugated copper, 3/8 in, black PE jacket<br>(Not for Individual Sale - Jumpers only) |
| P4HM-S2  | - | 4.3-10 Male for 3/8 in LSF2-50 cable, factory attached  |