

# MPT-A2A-BB-NN-500M

---



HELIAX® Power cable, with aluminum shield with quantity 2x6 mm<sup>2</sup> cores, flame resistant CPR Class B2ca s1, d2, a1 rated, 500 meters

- Available with different colors on demand

## Product Classification

<b>Regional Availability</b>	Europe
<b>Product Type</b>	Power cable
<b>Product Brand</b>	HELIAX®
<b>Ordering Note</b>	ANDREW® non-standard product
<b>Warranty</b>	For more information, please consult our Product Warranty guidelines

## General Specifications


<b>Application</b>	Remote radio head
<b>Cable Type</b>	Power
<b>Conductor Type, singles</b>	Stranded
<b>Conductors, quantity</b>	2
<b>Jacket Color</b>	Black
<b>Jacket Color, singles</b>	Blue   Brown
<b>Outer Shield (Tape) Material</b>	Al/PET tape

## Dimensions

<b>Cable Length</b>	500.024 m   1,640.5 ft
<b>Diameter Over Jacket</b>	9.677 mm   0.381 in
<b>Conductor Gauge</b>	6 mm <sup>2</sup> class 5

## Cross Section Drawing


# MPT-A2A-BB-NN-500M



## Electrical Specifications

**Safety Voltage Rating** 600 V

## Ordering Tree



### Notes

- \* this size is not available for 6, 8, or 12 core cable options.
- \*\* this size is not available for 8 and 12 core cable options.

## Material Specifications

# MPT-A2A-BB-NN-500M

---

<b>Ground Wire Material</b>	Annealed aluminum wires
<b>Insulation Material, singles</b>	Flame retardant PE
<b>Jacket Material</b>	Flame retardant PE   Low Smoke Zero Halogen (LSZH)
<b>Outer Shield (Braid) Coverage</b>	100 %
<b>Outer Shield (Tape) Material</b>	Al/PET tape

## Environmental Specifications

<b>Installation temperature</b>	-20 °C to +70 °C (-4 °F to +158 °F)
<b>Operating Temperature</b>	-40 °C to +90 °C (-40 °F to +194 °F)
<b>Storage Temperature</b>	-40 °C to +80 °C (-40 °F to +176 °F)
<b>Environmental Space</b>	Indoor/Outdoor
<b>Jacket UV Resistance</b>	UV stabilized

## Packaging and Weights

<b>Cable weight</b>	170.008 kg/km   114.24 lb/kft
---------------------	-------------------------------

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.andrew.com/ProductCompliance">www.andrew.com/ProductCompliance</a>
ROHS	Compliant
UK-ROHS	Compliant



## \* Footnotes

<b>Warranty</b>	For more information, please consult our Product Warranty guidelines
<b>Operating Temperature</b>	Specification applicable to non-terminated bulk fiber cable